

INSTALLATION INSTRUCTIONS

Chrome Radiator Grille Set (99000-99031-10V)

Weight: 850g

- ① : Chrome radiator cover
- ② : Chrome radiator lower cover
- ③ : M6x10 mm truss-head screw
(on existing radiator grille)
- ④ : Chrome M6x10 mm truss-head screw




Fig. 1

Removal

1. Loosen the leg shield on either side by removing the M4x25 mm tapping screw ⑤ at air inlet (Fig. 2) and the M6x15 mm flanged bolt ⑥ under the fairing extension assembly (Fig. 3).




Fig. 2




Fig. 3

2. Loosen the side cowling cover assembly by removing M4x16 mm truss-head screws ⑦, each complete with a plain washer (Fig. 4) and M4x40 mm pan-head screw ⑧, complete with plain washer.



Fig. 4

INSTALLATION INSTRUCTIONS

3. Repeat the above two steps on the opposite side.
4. Referring to Figs. 5 and 6, remove the existing radiator grille by removing M6x10 mm truss-head screws ③. Also remove the existing radiator lower cover by removing its three M6x10 mm truss-head screws.




Fig. 5




Fig. 6

Mounting

5. Using the four screws ③ removed in step 4 and three more screws ④ (chrome M6x10 mm truss-head screws), install the chrome radiator grille ① and its lower cover ②. (Fig. 7–9)





Fig. 7



- ① : Chrome radiator grille
- ② : Chrome radiator lower cover
- ③ : M6x10 mm truss-head screw
(re-use removed screws)
- ④ : Chrome M6x10 mm truss-head screw

Fig. 8

6. Re-install the side cowling cover assembly and leg shield by carrying out the removal sequence of steps in the reverse order.




Fig. 9 Chrome radiator grille set in place