


Notice to Dealer:


This guide provides you with necessary information to install SUZUKI/Clarion Audio System optional parts on the motorcycle and should be read carefully and fully understood before proceeding with installation.

PARTS LIST

Front seat headset
junction harness



Back seat headset
junction harness



Connector holder
(2 pieces)

INSTALLATION

1. (1) Remove the machine screw and then the left side cover as shown in Fig. 1 (Pull it towards you, and then push it down).
- (2) Remove the right side cover in the same way.




Fig. 1

2. (1) Remove the right and left side trunk lids, the hexagon bolts and the seat, as shown in Fig. 2.
- (2) Disconnect the tube located under the seat.




Fig. 2

3. (1) Remove the screws and then the upper cover assembly as shown in Fig. 3.




Fig. 3

4. (1) Pull the sealing rubber off.
 (2) Remove the screws, and then the right and left cover assembly frames as shown in Fig. 4.




Fig. 4

IN GUIDE

**FRONT AND BACK SEAT HEADSET
JUNCTION HARNESS**

TOOLS REQUIRED

- #2 Phillips screwdriver
- Electric drill
- 12 mm dia. drill
- 10 mm and 13 mm box wrench

INSTALLATION NOTES

- Turn off the motorcycle ignition switch before starting.
- Follow the order indicated in the "INSTALLATION" section.
- Attach all connectors securely.
- Place the cords so that they don't get pinched or pressed.
- Fasten all bolts and nuts securely.

- 5**
- (1) Connect the audio case side headset harness with the back seat headset junction harness.
 - (2) Place cables for the back seat headset junction harness as shown in Fig. 5.
 - (3) Stick the connector holder to the bottom of the rear remote controller.
NOTE: Wipe clean the bottom of the rear remote controller with a cloth before sticking the connector holder to it.
 - (4) Insert the connector with waterproof cover into the connector holder.




Fig. 5

- 6.** (1) Perforate the cover assembly left frame at the places indicated in Fig. 6.




Fig. 6

- 7.** (1) Connect the audio case side headset harness with the front seat headset junction harness, as shown in Fig. 7.
 (2) Pass the junction harness' connector with waterproof cover through the hole drilled in the cover assembly left frame, and cover the hole with a grommet.
NOTE: The part number you should ask for when purchasing the grommet is: 09308-08007
 (3) Install the right and left cover assembly frames following the demounting procedure in reverse.
 (4) Stick the connector holder to the top of the left frame of the cover assembly.
NOTE: Wipe clean the place chosen on the frame before sticking the holder to it.
 (5) Insert the junction harness' connector into the connector holder.




Fig. 7

- 8.** Connect the headset to the junction harness, turn on all switches and check functioning of the headset's headphones and microphone while operating your main audio unit.
9. Turn off all switches after checking.
10. Install all motorcycle parts following the demounting procedure in reverse.